

Suction Trailer 700-1500-2100



The new Suction system is suitable for unblocking and cleaning of drains and sewers.

Welded steeltank with tank diameter \varnothing 1.100 mm; thickness 5 mm.

The waste water tank is provided with rear door on the back which can be opened and closed by means of 4 pinch screws.

The rear door has 3 sightglasses of \varnothing 3" (3 levels), a drainvalve \varnothing 3" with quick shutter and Bauer coupling on the bottom side of the tank and a suction valve \varnothing 3" with quick Bauer coupling on the top end of the tank.

Within the tank there is a floatball (\varnothing 60 mm) security system and on the outside of the tank a floatball chiffon (\varnothing 60 mm) is mounted.

Also a mano / vacuummeter is mounted on the suction line at the front side of the unit.

The tank and the rear cover are galvanized from the inside as well as the outside.

The underframe is made out of welded U-steel. On this underframe the tank is mounted and the suctionpump and petrolengine are mounted in front of the tank without any cover (so, it's an open construction). No hose storage nor toolboxes are mounted.

On both sides of the tank however, as well as on the rear cover, metal hooks (also galvanized) are mounted on which the suction hoses can be stored.



ΚΑΜΑ ΕΛΛΑΣ Ε.Π.Ε.
ΑΝΤΙΠΡΟΣΩΠΕΙΕΣ
ΝΑΡΚΙΣΣΟΥ 13
570 13 ΩΡΑΙΟΚΑΣΤΡΟ
ΤΗΛ. 2310-69.8962
ΦΑΞ. 2310-69.90.71

Technical details

Drive	Briggs & Stratton 18 hp, Honda 20 hp petrol engine.
Pump	Gardner Denver Wittig SLS 54 with capacity 5.400 liter air/min. Suction capacity \pm 0,8 bar and pressure 0,5 bar or Battioni Pagani MEC 5000 & 9000 with capacity 5.000 & 9.030 liter air/min. Suction capacity \pm 0,8 bar and pressure 0,5 bar
Tank	There are more variant possible, tank sizes as of 700 ltr up to 2.100 ltr.
Standard accessories	2 pieces of \pm 2,5 m suction hose 3" with Bauer couplings. 1 PVC suction tube length \pm 1,5m with ball valve and Bauer coupling. Tool for (un)screwing pinches from the rear door.
Weight	Approx 500 kg.
Dimensions	Approx 1.700 X 1.015 X 1.195 mm. (L x W x H)

Rioned

Rior B.V./Rioned
Postbus 5070
5004 EB Tilburg
Centaurusweg 45
5015 TC Tilburg
Nederland

Tel. +31 (0)13 547 91 00
Fax +31 (0)13 547 91 04

info@rioned.com
www.rioned.com

Rioned UK Limited
23 James Carter Road
Mildenhall, Suffolk, IP28 7DE
United Kingdom

Tel. +44 (0)1638 713 800
Fax +44 (0)1638 716 863

sales@rioned.co.uk
www.rioned.co.uk